






Model	Rated current (A)	Rated voltage (V)	Rated power (W)
BPL.4	32	500	16000
BPL.4	32	300	9600
BPL.4	20	500	10000
BPL.4	20	300	6000
BPL.4	16	500	8000
BPL.4	16	300	4800
BPL.4	12	500	6000
BPL.4	12	300	3600
BPL.4	8	500	4000
BPL.4	8	300	2400

Il presente catalogo è un documento di riferimento per il cliente. Cabur non si assume alcuna responsabilità per l'uso non corretto delle informazioni contenute in questo documento. Cabur si riserva il diritto di modificare senza preavviso le informazioni contenute in questo documento. Cabur si riserva il diritto di non pubblicare tutte le informazioni contenute in questo documento. Cabur si riserva il diritto di non pubblicare tutte le informazioni contenute in questo documento.

modular multi-pole terminal, 4 mm², beige

Series	BPL-TPL
Code	BP200
Type	BPL/R
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through 2 poles
Rated cross-section	4 mm ²
Rated cross-section	
Connecting capacity	
Flexible wire	0.5-4 mm ²
Rigid wire	0.5-6 mm ²
Wire with ferrule - ferrule type	4 mm ² - WP40/16
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	32 A
Caliber	A4
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	300 V
Maximum current (rated cross-section)	20 A
Section (min-max)	18-12 (AWG)
Tightening torque value (UL)	4.4 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	320 V
Maximum current (rated cross-section)	32 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	9 mm
Tightening torque value (nom. / max.)	0.5 / 0.7 Nm
Dimension	13x24x26 mm (AxBxH)
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	-
Insulated bushing	-
APPROVALS AND MARKINGS	  



* Panel mountable with M3 screw (max. 5.6 mm head diameter)* With dovetail joint for multiple connection
1 (1) When using BPL.4 and TPL.4 terminal blocks in Ex e classified installations, is required the insulated fixing screw

DESCRIZIONE DEL PRODOTTO

modular multi-pole terminal, 4 mm², beige