




multi-pole terminal, 2.5 mm², beige

Series	CF
Code	CF400
Type	CF.8/2+2
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	2.5 mm ²
Rated cross-section	
Connecting capacity	
Flexible wire	< 2.5 mm ²
Rigid wire	-
Wire with ferrule - ferrule type	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	20 A
Caliber	-
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Operating temperature Min/Max	-
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	-
Tightening torque value (nom. / max.)	-
Dimension	34x80x24 mm (AxBxH)
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	-
Insulated bushing	CF/BI (cod. CF102), CF/BR (cod. CF201) (1)
APPROVALS AND MARKINGS	



* With 6.3 x 0.8 mm flat push-on tab connections (2 for each pole)* Singular or overlapped mounting
1 (1) Per maggiori dettagli, consultare le nostre esplicative

DESCRIZIONE DEL PRODOTTO

multi-pole terminal, 2.5 mm², beige