





screw terminal for junction boxes, 35 mm<sup>2</sup>

|                                                                                   |                                                                                     |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Series</b>                                                                     | CONTC                                                                               |
| <b>Code</b>                                                                       | CONTC35                                                                             |
| <b>Type</b>                                                                       | CONT/35                                                                             |
| <b>Colour</b>                                                                     | Transparent                                                                         |
| <b>HS code</b>                                                                    | 85369010                                                                            |
| <b>TECHNICAL FEATURES</b>                                                         |                                                                                     |
| <b>Function/Type</b>                                                              | Branch terminal                                                                     |
| <b>Rated cross-section</b>                                                        | 35 mm <sup>2</sup>                                                                  |
| <b>Rated cross-section</b>                                                        |                                                                                     |
| <b>Connecting capacity</b>                                                        |                                                                                     |
| <b>N poles</b>                                                                    | 1                                                                                   |
| <b>Flexible wire</b>                                                              | -                                                                                   |
| <b>Rigid wire</b>                                                                 | -                                                                                   |
| <b>Electrical characteristics according to IEC EN standard</b>                    |                                                                                     |
| <b>Maximum voltage AC/DC</b>                                                      | 750 V                                                                               |
| <b>Maximum current (rated cross-section)</b>                                      | 125 A                                                                               |
| <b>Caliber</b>                                                                    | -                                                                                   |
| <b>Electrical characteristics according to ATEX directive and IEC Ex standard</b> |                                                                                     |
| <b>Protection degree</b>                                                          | IP20                                                                                |
| <b>Insulation stripping length</b>                                                | -                                                                                   |
| <b>Dimension</b>                                                                  | 46x14x25x44 mm (AxBxCxD)                                                            |
| <b>Insulation material temperature index (EN 60216-1)</b>                         | 130 °C                                                                              |
| <b>Plastic material</b>                                                           | Polycarbonate UL94V-0                                                               |
| <b>ACCESSORIES</b>                                                                |                                                                                     |
| <b>APPROVALS AND MARKINGS</b>                                                     |  |



\* Multipoles strip, easily separable\* Transparent and self-extinguishing body\* High dielectric strength\* IP20 protection degree  
1 (1) Strip with 10 separable terminals

## DESCRIZIONE DEL PRODOTTO

screw terminal for junction boxes, 35 mm<sup>2</sup>