


Cartridge with diode 1 A, suitable for MF100, MF100GR, DA100, DA100GR, HF300GR

Series	CPF
Code	CPF501
Type	CPF/5D1A
HS code	85389099
TECHNICAL DATA	
Typology	Component-holder cartridge
Sub-typology	with 1 A diode
Colour	Green
Package qty.	20
Material	Polyamide UL94-V0
Width (pitch)	6 mm
Length	33 mm
Height	(2)
Current	1 A
Voltage	320 V
Correlations	MF100, MF100GR, DA100, DA100GR, HF300GR

MAX. DISSIPATED POWER IN CONJ. WITH THE CONTACTS				
Series	HMFA.1	HMFA.2	HMFA.3	HMFA.4
Power (W)	200	200	200	200
CPF501	1.2	1.2	1.2	1.2
CPF501 (with end plate)	1.2	1.2	1.2	1.2
CPF501 (with end plate and diode)	1.2	1.2	1.2	1.2
CPF501 (with end plate and diode, 100°C)	1.2	1.2	1.2	1.2
CPF501 (with end plate and diode, 125°C)	1.2	1.2	1.2	1.2
CPF501 (with end plate and diode, 150°C)	1.2	1.2	1.2	1.2

Utilizzo su morsetti HMFA.2:
 inserire una piastrina terminale tra due morsetti adiacenti, a causa del maggior spessore della cartuccia.

Use on HMFA.2 terminal blocks:
 insert an end plate between two adjacent terminal blocks, due to the greater thickness of the cartridge.



2 (2) the height depends on the mounting on relative terminal blocks and the din rail (see table)

DESCRIZIONE DEL PRODOTTO

Cartridge with diode 1 A, suitable for MF100, MF100GR, DA100, DA100GR, HF300GR