



MAX. DISPERSED POWER IN COMP. WITH REC. CARTRIDGE				
Series	HMFA.2	HMFA.2	HMFA.2	HMFA.2
Model	CPF512	CPF512	CPF512	CPF512
Dimensions	20	20	20	20
Series	L3	L3	L3	L3
Series	L4	L4	L4	L4
Series	L5	L5	L5	L5
Series	L6	L6	L6	L6
Series	L7	L7	L7	L7
Series	L8	L8	L8	L8
Series	L9	L9	L9	L9
Series	L10	L10	L10	L10
Series	L11	L11	L11	L11
Series	L12	L12	L12	L12
Series	L13	L13	L13	L13
Series	L14	L14	L14	L14
Series	L15	L15	L15	L15
Series	L16	L16	L16	L16
Series	L17	L17	L17	L17
Series	L18	L18	L18	L18
Series	L19	L19	L19	L19
Series	L20	L20	L20	L20

Utilizzo su morsetti HMFA.2:
 inserire una piastrina terminale tra due morsetti adiacenti, a causa del maggior spessore della cartuccia.

Use on HMFA.2 terminal blocks:
 insert an end plate between two adjacent terminal blocks, due to the greater thickness of the cartridge.

Cartridge with alarm LED 12 V, suitable for MF100, MF100GR, DA100, DA100GR, HF300GR

Series	CPF
Code	CPF512
Type	CPF/5L12
HS code	85389099
TECHNICAL DATA	
Typology	Component-holder cartridge
Sub-typology	with 12 V alarm LED
Colour	Green
Package qty.	20
Material	Polyamide UL94-V0
Width (pitch)	6 mm
Length	33 mm
Height	(2)
Current	6,3 A
Voltage	320 V
Correlations	MF100, MF100GR, DA100, DA100GR, HF300GR



1 (1) with fuse $\varnothing 5 \times 20$ mm, 250 V, $I_{max} = 6,3$ A – with brass pin $I_{max} = 10$ A2 (2) the height depends on the mounting on relative terminal blocks and the din rail (see table)

DESCRIZIONE DEL PRODOTTO

Cartridge with alarm LED 12 V, suitable for MF100, MF100GR, DA100, DA100GR, HF300GR