


Cartridge with alarm LED 24 V, suitable for MF100, MF100GR, DA100, DA100GR, HF300GR

Series	CPF
Code	CPF524
Type	CPF/5L24
HS code	85389099
TECHNICAL DATA	
Typology	Component-holder cartridge
Sub-typology	with 24 V alarm LED
Colour	Green
Package qty.	20
Material	Polyamide UL94-V0
Width (pitch)	6 mm
Length	33 mm
Height	(2)
Current	6,3 A
Voltage	320 V
Correlations	MF100, MF100GR, DA100, DA100GR, HF300GR

Series	HMFA.1	HMFA.2	HMFA.3
HMFA.1	20	20	20
HMFA.2	12	12	12
HMFA.3	12	12	12

Utilizzo su morsetti HMFA.2:
 inserire una piastrina terminale tra due morsetti adiacenti, a causa del maggior spessore della cartuccia.

Use on HMFA.2 terminal blocks:
 insert an end plate between two adjacent terminal blocks, due to the greater thickness of the cartridge.



1 (1) with fuse \varnothing 5 x 20 mm, 250 V, $I_{max} = 6,3$ A – with brass pin $I_{max} = 10$ A2 (2) the height depends on the mounting on relative terminal blocks and the din rail (see table)

DESCRIZIONE DEL PRODOTTO

Cartridge with alarm LED 24 V, suitable for MF100, MF100GR, DA100, DA100GR, HF300GR