





## EV charger Compact 7kW with type 2 plug

<b>Series</b>	COMPACT
<b>Code</b>	EVCOMP7S
<b>Type</b>	EVCOMP7S
<b>HS code</b>	85437090
<b>PRODUCT INFORMATION</b>	
<b>Power</b>	3.5 -7.4 kW
<b>Charging Mode</b>	MODE 3 CASE B (no cable)
<b>Socket</b>	Type 2
<b>Dimensions (W x H x D)</b>	160x125x210 mm
<b>Weight</b>	2.3 Kg
<b>Enclosure Material</b>	PC+ASA (UL94-V0)
<b>Mounting</b>	Wall
<b>GENERAL FEATURES</b>	
<b>Voltage</b>	230 V ±15%
<b>Frequency</b>	50/60Hz
<b>Network Configuration</b>	TN/TT/IT (IT only supports voltage between L and L < 240VAC)
<b>Earth Leakage Protection</b>	DC Leak (6 mA)
<b>User interface</b>	APP Control
<b>Start/Stop Charge</b>	Plug-in
<b>Communications signals</b>	LED Light belt (red, blue, green)
<b>Power metering</b>	None
<b>Additional</b>	Wifi (Access Point) Hotspot
<b>Power Management</b>	Static (Max power adjustable by App or selector)
<b>PhotoVoltaic integration</b>	-
<b>Dry contact</b>	-
<b>Communication Protocol</b>	None
<b>Background Functions</b>	WIFI system upgrade
<b>Reports</b>	Charge reports / Fault reports
<b>Protections</b>	Overcurrent protection; Overvoltage protection; Undervoltage protection; Relay over temperature protection; Socket or plug over temperature protection; CP fault protection; Relay adhesion protection
<b>IP Degree</b>	IP54
<b>IK Protection degree (20°C)</b>	IK12
<b>Ambient Temperature</b>	-25°C +50°C
<b>Operating Humidity</b>	≤95%HR
<b>Standards</b>	IEC 61851-1; IEC 61851-21-2 (EMC class B); IEC 62196-2; EN 300 328 (RED WiFi 2.4GHz); EN 301 489-1/17 (RF-EMC); EN 62311 (Health)
<b>APPROVALS AND MARKINGS</b>	CE, 



\* Stylish and compact design\* Charging Mode: MODE 3, with type 2 socket (CASE B)\* Connector standard Type 2\* WI-FI connectivity in Access Point mode\* Plug in start charging\* Web App configuration management\* DC Earth Leakage Protection 6mA\* Wall mounting

## DESCRIZIONE DEL PRODOTTO

EV charger Compact 7kW with type 2 plug