




screw terminal block fuse-holder with alarm signal, 10 mm<sup>2</sup>, beige



<b>Series</b>	SFR – CBF – FPL
<b>Code</b>	FP923
<b>Type</b>	FPL10/C230
<b>HS code</b>	85369010
<b>Colour</b>	Beige
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Fuse-holder 6.3×32 with alarm
<b>Rated cross-section</b>	10 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>Flexible wire</b>	1.5-16 mm <sup>2</sup>
<b>Rigid wire</b>	1.5-16 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	10 mm <sup>2</sup> – WP100/21
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	800 V
<b>Maximum current (rated cross-section)</b>	10 A
<b>Caliber</b>	B6
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	300 V
<b>Maximum current (rated cross-section)</b>	15 A
<b>Section (min-max)</b>	20-6 (AWG)
<b>Tightening torque value (UL)</b>	7 lb.in
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Rated impulse withstand voltage / pollution degree</b>	6 kV / 3
<b>Insulation stripping length</b>	14 mm
<b>Tightening torque value (nom. / max.)</b>	1.2 / 1.9 Nm
<b>Width (pitch)</b>	12 mm
<b>Length</b>	63 mm
<b>Height mounted on TH35-7.5/TH35-15/G32</b>	71 / 79 / 75 mm
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
<b>Grey</b>	–
<b>Blue</b>	–
<b>Beige</b>	–
<b>Thickness</b>	–
<b>Cross-connection</b>	
<b>Model A)</b>	–
<b>Model B)</b>	–
<b>Rated current carrying capacity IEC/ATEX</b>	–
<b>Cross-connection identification strip</b>	–
<b>Coloured partition plate</b>	DFU/6/R (cod. DU06R)
<b>Cross-connection barrier</b>	–
<b>Test plug socket</b>	–
<b>Test plug</b>	–
<b>Connection knob</b>	MSM (cod. FC103)
<b>Marking</b>	
<b>Snap-on numbering strip</b>	–
<b>Single marking tag</b>	–
<b>Fuse type</b>	6.3×32 mm (1)
<b>Conductive element</b>	–
<b>Light alarm circuit (12...48 V)</b>	–
<b>Light alarm circuit (110...230 V)</b>	Already mounted
<b>End bracket</b>	
<b>TH35 screw type</b>	BT/3 (cod. BT003)
<b>TH35 snap-fit type</b>	BTO (cod. BT007)
<b>TH35 and G32 snap-fit type</b>	BTU (cod. BT005)
<b>Mounting rail</b>	
<b>IEC 60715/TH35</b>	PR/3/...
<b>IEC 60715/G32</b>	–
<b>APPROVALS AND MARKINGS</b>	 



\* Suitable for 5x20 mm fuses\* Alarm LED circuit already mounted (12-48 V)\* Fuse available separately  
1 For more details on accessories, refer to the relevant chapters

## DESCRIZIONE DEL PRODOTTO

screw terminal block fuse-holder with alarm signal, 10 mm<sup>2</sup>, beige