




High current terminal screw connection, 240 mm², beige

Series	GPA
Code	GF300
Type	GPA.240/FIX
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	240 mm ²
Connecting capacity	
Flexible wire	95-240 mm ²
Rigid wire	50-300 mm ²
Wire with ferrule - ferrule type	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	415 A
Caliber	B16
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	415 A
Section (min-max)	3/0-600 MCM (AWG)
Tightening torque value (UL)	300 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Operating temperature Min/Max	-
ensione impulsiva nom. / grado di inquinamento	12 kV / 3
Insulation stripping length	40 mm
Tightening torque value (nom. / max.)	-
Width (pitch)	37 mm
Length	-
Height mounted on TH35-7.5/TH35-15/G32	
Height for panel mounting	-
Length mounted on panel	134 mm
Fixing distance between center	118 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
Cross-connection	
Model A)	-
Model B)	-
Rated current carrying capacity IEC/ATEX	-
Multiple cross-connection bar	-
Shunting screw and sleeve (Standard / Exe)	-
Protection cover	-
Coloured partition plate	-
Test plug socket	-
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	-
TH35 snap-fit type	-
TH35 and G32 snap-fit type	-
Mounting rail	
IEC 60715/TH35	-
IEC 60715/G32	-
APPROVALS AND MARKINGS	



* Panel mounting by means of M6 screws

DESCRIZIONE DEL PRODOTTO

High current terminal screw connection, 240 mm², beige