




High current terminal screw connection, 70 mm², beige

Series	GPA
Code	GF400
Type	GPA.70/FIX
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	70 mm ²
Connecting capacity	
Flexible wire	10-95 mm ²
Rigid wire	10-95 mm ²
Wire with ferrule - ferrule type	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	192 A
Caliber	B11
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	215 A
Section (min-max)	8-4/0 (AWG)
Tightening torque value (UL)	79.5 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Operating temperature Min/Max	-
ensione impulsiva nom. / grado di inquinamento	12 kV / 3
Insulation stripping length	25 mm
Tightening torque value (nom. / max.)	-
Width (pitch)	20.5 mm
Length	-
Height mounted on TH35-7.5/TH35-15/G32	-
Height for panel mounting	-
Lenght mounted on panel	102 mm
Fixing distance between center	88 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
Cross-connection	
Model A)	POF/70 (cod. P0F70)
Model B)	-
Rated current carrying capacity IEC/ATEX	192 A
Multiple cross-connection bar	PMP/08 (cod. PMP08)
Shunting screw and sleeve (Standard / Exe)	CPM/70 (cod. CPM70) 12 poles
Protection cover	PRP/08 (cod. PRP08)
Coloured partition plate	DF/GPA/70/R (cod. DU070R)
Test plug socket	SDD/2 (cod. DD002) - PSD/C (cod. PD003)
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	-
TH35 snap-fit type	-
TH35 and G32 snap-fit type	-
Mounting rail	
IEC 60715/TH35	-
IEC 60715/G32	-
APPROVALS AND MARKINGS	
	  



* Panel mounting by means of M6 screws* GPA.70 allow to create parallel connections

DESCRIZIONE DEL PRODOTTO

High current terminal screw connection, 70 mm², beige