


For insulation, wiring, protection, For home, auto, industrial, and nautical use, Working temperature: -55°C to +125°C, Shrink temperature: +70°C, Shrink ratio: 2:1, „



|                    |                                      |
|--------------------|--------------------------------------|
| <b>Code</b>        | GTF095075W                           |
| <b>Description</b> | polyolefin flex self-ext UL 2:1 125° |
| <b>HS code</b>     | 54022000                             |
| <b>Colour</b>      | White                                |
| <b>Nominal ø</b>   |                                      |
| <b>mm2</b>         | 9,5                                  |
| <b>Mt pk.</b>      | 75                                   |



\* For insulation, wiring, protection\* For home, auto, industrial, and nautical use\* Working temperature: -55°C to +125°C\* Shrink temperature: +70°C\* Shrink ratio: 2:1  
**1** The shrinking operation is achieved with a temperature of over 70 degrees, obtained with a hot-air dryer or an indirect flame. The sleeves adhere perfectly to the object(s) that need to be covered, united, or protected.



## DESCRIZIONE DEL PRODOTTO

To combine, cover, and protect conductors, terminations, and components.

For insulation, wiring, protection, For home, auto, industrial, and nautical use, Working temperature: -55°C to +125°C, Shrink temperature: +70°C, Shrink ratio: 2:1, „