



Sping-clamp
terminal block 2.5mm², 1-level, blue color, intermediate model

| | |
|---|-------------------------------|
| Series | HPP – HP |
| Code | HI130 |
| Type | HP.2 (Ex)i |
| HS code | 85369010 |
| Colour | blue |
| TECHNICAL FEATURES | |
| Function/Type | Feed-through |
| Rated cross-section | 2.5 mm ² |
| Connecting capacity | |
| Flexible wire | 0.2-4 mm ² |
| Rigid wire | 0.2-4 mm ² |
| Wire with ferrule - ferrule type | 2.5 mm ² – WP25/14 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 800 V |
| Maximum current (rated cross-section) | 24 A |
| Caliber | A3 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 20 A / 24 A |
| Section (min-max) | 28-12 (AWG) |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | 630 V |
| Maximum current (rated cross-section) | 24 A |
| Operating temperature Min/Max | -40 °C / +80 °C |
| Rated impulse withstand voltage / pollution degree | 8 kV / 3 |
| Insulation stripping length | 10 mm |
| Width (pitch) | 5.2 mm |
| Length | 36 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | - / - / - |
| Height mounted on TH15-5.5 | - |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | HPV/PT/GR (cod. HV111GR) |
| Blue | - |
| Thickness | 1.5 mm |
| Cross-connection | |
| Model A) | PTC/03/... (cod. PTC03...) |
| Model B) | - |
| Rated current carrying capacity IEC/ATEX | 24 A |
| Cross-connection identification strip | PTC/SP (cod. PTC0990) |
| Coloured partition plate | DFP/2/R (cod. DFP2R) |
| Cross-connection barrier | SDD/1 (cod. DD001) |
| Test plug | SDD/1 (cod. DD001) |
| Modular test plug | SDH/5 (cod. DH005) |
| End section for modular test plug | SH5/PT (cod. DH501) |
| Marking | |
| Single marking tag | SHZ/2 (cod. SH001) |
| Single marking tag for pitch insertion | - |
| End bracket | |
| TH35 screw type | - |
| DIN rail according to IEC 60715/TH15 | - |
| APPROVALS AND MARKINGS | |



* Compact dimension* Suitable for PR/2 series DIN rail according to IEC60711/TH16
1 For more details on accessories, refer to the relevant chapters 2 (1) With interlocking for snapping on HPP.2 and HPC.2

DESCRIZIONE DEL PRODOTTO

HP.2(EX)I Sping-clamp
terminal block 2.5mm², 1-level, blue color, intermediate model