



AC surge protection device, type II, nominal voltage: 220 - 230 V

Series	ISPD
Code	ISPD255ACNPE
Type	ISPD255ACNPE
HS code	85354000
TECHNICAL FEATURES	
Test class	II
Type of Network	TN, IT, TT
Nominal voltage Un	220 - 230 (V)
Max. continuous voltage	255 (V)
Working frequency	50 - 60 (Hz)
Max. Discharge current (8/20 μ s)	60 (kA)
Nominal discharge current (8/20 μ s)	30 (kA)
Voltage protection level at In	1.5 (kV)
Protection mode	N-PE
Isolation resistance	> 10 ² (M Ω)
Response time	\leq 100 (ns)
Recommended back-up fuse	125 (1) (A)
Max. cables section	25 (mm ²)
Mounting Guida TH35	Yes
Working temperature	-40...+70 °C
Protection degree	IP20
Housing material	PPO
Inflammability class	UL94-V0
Fault indicator	
Green LED	OK
Red LED	Fail
Dimensions (LxHxD)	18x90x66
Quantity / Package	1 piece
ACCESSORIES	
2 poles	9000582
3 poles	9000583
4 poles	9000584
APPROVALS AND MARKINGS	
	CE



* For single phase and three phase systems

1 (1) the fuses is not mandatory on all plants, if it's necessary choose one that match correctly with the system

DESCRIZIONE DEL PRODOTTO

AC surge protection device, type II, nominal voltage: 220 - 230 V