




Single  
phase panel with SPD and MCB 32A max.

<b>Series</b>	ISS
<b>Code</b>	ISS00MNNA03320
<b>Type</b>	ISS00MNNA03320
<b>HS code</b>	85372091
<b>AC CIRCUIT</b>	
<b>Max. Input Voltage</b>	230 (V)
<b>Max. input current</b>	32 (A)
<b>Nominal frequency</b>	50 (Hz)
<b>Thermal - magnetic circuit breaker</b>	
<b>Type</b>	1P+N
<b>Flow Rate</b>	32 (A)
<b>Tripping curve</b>	C
<b>Short circuit current</b>	10 (kA)
<b>Residual-current circuit breaker</b>	
<b>Class</b>	A
<b>Sensitivity</b>	0.3 (A)
<b>Surge protective device</b>	
<b>Nominal voltage Un</b>	230 (V)
<b>Protection level Up</b>	1500 (V)
<b>Nominal discharge current 8/20 In</b>	20 (kA)
<b>Input connection</b>	circuit breaker terminals
<b>Output connection</b>	circuit breaker terminals
<b>GENERAL DATA</b>	
<b>Protection degree</b>	IP65
<b>Size (including connectors)</b>	275x111x200 (mm)
<b>Standard compliancy</b>	CEI EN 61439-2



\* A-class Residual-Current Circuit Breaker\* 10 kA Thermal-Magnetic Circuit Breaker\* AC surge protective device\* CEI EN 61439-2 compliant

## DESCRIZIONE DEL PRODOTTO

ISS00MNNA03320 Single phase panel with SPD and MCB 32A max.