



unipolar distribution terminal board, 160A, grey

Series	QBLOK
Code	QBLOK1P160
Type	QBLOK1P160A6
Colour	Grey
TECHNICAL FEATURES	
Function/Type	Distribution terminal board
Number and rated cross connection	
A	
B	
C	
D	-
Input A	
Rated cross-section	1 x 70 mm ²
Connecting capacity (flexible)	10-70 mm ²
Connecting capacity (rigid)	10-70 mm ²
Connecting capacity (with ferrule)	50 mm ² – WP 350/40
Supply bar dimension	15 x 5 mm
Output B	
Rated cross-section	2 x 25 mm ²
Connecting capacity (flexible)	2.5–25 mm ²
Connecting capacity (rigid)	2.5–25 mm ²
Connecting capacity (with ferrule)	16 mm ² (WP 160/22)
Output C	
Rated cross-section	3 x 16 mm ²
Connecting capacity (flexible)	1.5–16 mm ²
Connecting capacity (rigid)	1.5–16 mm ²
Connecting capacity (with ferrule)	10 mm ² (WP 100/21)
Output D	
Rated cross-section	-
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	1000 Vac / 1000 Vdc
Maximum current (rated cross-section)	192 A
Caliber	-
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 Vac
Maximum current (rated cross-section)	160 A
Section (min-max)	(1)
Tightening torque value (UL)	(1)
Short term current allowed (I_{cw}) (value effective for 1s)	3 kA
Peak current (I_{pk})	
Rated impulse withstand voltage / pollution degree	8kV / 3
Insulation stripping length	17/12/12 mm (2)
Tightening torque value (nom. / max.)	10/3/-/ - Nm (2)
Plastic material	Polyamide, polycarbonate
Width (pitch)	41 mm
Length	74.5 mm
Height mounted on TH35-7.5/TH35-15	45.4 / 52.4 mm
Height for panel mounting	45.4 mm
ACCESSORIES	
Marking	
Single marking tag	-
Marking tag	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	-
Mounting rail	
DIN rail according to IEC 60715/TH35	-
IEC 60715/TH35	PR/3/...
APPROVALS AND MARKINGS	UL, CE, etc.



* Easy cabling thanks to an innovative design with a graduated brass body* DIN rail and panel mountable, with dovetail joint for multiple connection* Available entries for wire or metal bar* IP20 protection degree* Captive tightening screw
1 (1) For more details, refer to the data sheet 2 (2) Values referred to the A/B/C/D connections

DESCRIZIONE DEL PRODOTTO

unipolar distribution terminal board, 160A, grey