



unipolar distribution terminal board, 7 x 10 mm², grey

Caulan	ODLOV
Series Code	QBLOK OPLOK7003
Code	QBLOK7/003
Type	QBLOK.7/GR
HS code	85369010
Colour	Grey
TECHNICAL FEATURES	Dietalkutien tenneine I beend
Function/Type	Distribution terminal board
Number and rated cross connection	
<u>A</u>	
<u>B</u>	
<u>C</u>	
<u>D</u>	<u>-</u>
Input A	
Rated cross-section	7 x 10 mm²
Connecting capacity (flexible)	1.5-10 mm²
Connecting capacity (rigid)	1.5-16 mm²
Connecting capacity (with ferrule)	10 mm² – WP 100/21
Supply bar dimension	
Output B	
Rated cross-section	=
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	=
Output C	
Rated cross-section	-
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Output D	
Rated cross-section	_
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	63 A
Caliber	B5
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	_
Short term current allowed (Icw) (value effective for 1s)	
Peak current (lpk)	
Rated impulse withstand voltage / pollution degree	- -
Insulation stripping length	6 mm
Tightening torque value (nom. / max.)	2 / 2.5 Nm
Plastic material	Polyamide UL94V-0
Widht (pitch)	16 mm
Length	53 mm
Height mounted on TH35-7.5/TH35-15	33 / 41 mm
Height for panel mounting	-
ACCESSORIES	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S)
Marking tag	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type TH35 and G32 snap-fit type	BTO (cod. BT007) BTU (cod. BT005)
	DTU (COU. DTUUS)
Mounting rail	_
DIN rail according to IEC 60715/TH35	
IEC 60715/TH35	PR/3/
APPROVALS AND MARKINGS	₩,

QBLOK7003



* IP20 protegtion degree* Marking possible with a CNU/8 or CNU/10 tag* Available in grey, green and blue colors* Self-extinguishing plastic material 1 For more details, refer to the data sheet

DESCRIZIONE DEL PRODOTTO

unipolar distribution terminal board, 7 x 10 mm², grey