




distribution terminal boards unipolar, 2 x 2.0 mm², green

Series	POLM
Code	QPOL1204
Type	POLM.1215/TE
Colour	Green
TECHNICAL FEATURES	
Function/Type	Distribution terminal board
Input A	
Rated cross-section	2 x 2.0 mm ²
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Output B	
Rated cross-section	12 x 1.5 mm ²
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Output C	
Rated cross-section	1 x 1.0 mm ²
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Output D	
Rated cross-section	-
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	80 A
Caliber	-
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Rated impulse withstand voltage / pollution degree	-
Insulation stripping length	-
Tightening torque value (nom. / max.)	-
Plastic material	Polyamide
Width (pitch)	-
Length	-
Height mounted on TH35-7.5/TH35-15	- / -
ACCESSORIES	
Marking	
Single marking tag	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
APPROVALS AND MARKINGS	



* DIN rail and panel mountable

DESCRIZIONE DEL PRODOTTO

distribution terminal boards unipolar, 2 x 2.0 mm², green