







| SERIE MODELLO DESCRIZIONE DIMENSIONI (mm) PRESSIONE (N) MONTAGGIO | | | |
|---|---------------------|-----------------|---------------|
| Modello | Descrizione | Dimensioni (mm) | Pressione (N) |
| TE.16/D | 16 mm ² | 46,5 | 13 |
| TE.25/D | 25 mm ² | 46,5 | 13 |
| TE.35/D | 35 mm ² | 46,5 | 13 |
| TE.50/D | 50 mm ² | 46,5 | 13 |
| TE.70/D | 70 mm ² | 46,5 | 13 |
| TE.95/D | 95 mm ² | 46,5 | 13 |
| TE.120/D | 120 mm ² | 46,5 | 13 |
| TE.160/D | 160 mm ² | 46,5 | 13 |

screw terminal block 1 level earth connection, 16 mm²

| | |
|---|--|
| Series | TE |
| Code | TE210 |
| Type | TE.16/D |
| HS code | 85369010 |
| Colour | Yellow-green |
| TECHNICAL FEATURES | |
| Function/Type | Earth terminal blocks |
| Rated cross-section | 16 mm ² |
| Connecting capacity | |
| Flexible wire | 0.5-16 mm ² |
| Rigid wire | 0.5-25 mm ² |
| Wire with ferrule - ferrule type | 16 mm ² - WP160/22 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | - |
| Maximum current (rated cross-section) | - |
| Caliber | B7 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | - |
| Section (min-max) | 20-3 (AWG) |
| Tightening torque value (UL) | 13.3 lb.in |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | - |
| Maximum current (rated cross-section) | 76 A |
| Operating temperature Min/Max | -40 °C / +110 °C |
| Rated impulse withstand voltage / pollution degree | 8 kV / 3 |
| Insulation stripping length | 13 mm |
| Tightening torque value (nom. / max.) | 1.8 / 3 Nm |
| Width (pitch) | 12 mm |
| Length | 46,5 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | - / - / 57,5 mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | - |
| Green | - |
| Thickness | - |
| Cross-connection | |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S) |
| Single marking tag for pitch insertion | - |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| Mounting rail | |
| IEC 60715/TH35 | PR/3/... |
| IEC 60715/G32 | PR/DIN/... |
| APPROVALS AND MARKINGS | |
|      | |



DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level earth connection, 16 mm²

