



Double ferrules with insulated collars, 2,0 x 1,5 mm, black



| | |
|----------------|-----------|
| Code | WP90004 |
| HS code | 85369010 |
| Colour | Black |
| Section | |
| mm2 | 2,0 x 1,5 |
| D1 | |
| mm | 2,3 |
| D2 | |
| mm | 3,5 |
| D3 | |
| mm | 6,5 |
| L1 | |
| mm | 16,0 |
| L2 | |
| mm | 8,0 |
| S1 | |
| mm | 0,15 |
| S2 | |
| mm | 0,3 |
| Pcs Box | 500 |



1 The double slot series is made of tin-plated electrolytic copper with the insulated part in polypropylene, resistant up to 105°C. These terminals were designed for use in connections where a quick and safe connection is required. In fact, the current trend towards miniaturisation of electrical equipment makes these terminals particularly useful and economical. The special large housing slot is easily able to hold the bulk created by two wires.

DESCRIZIONE DEL PRODOTTO

Terminals with sleeves and insulated collars.

The double slot series is made of tin-plated electrolytic copper with the insulated part in polypropylene, resistant up to 105°C. These terminals were designed for use in connections where a quick and safe connection is required. In fact, the current trend towards miniaturisation of electrical equipment makes these terminals particularly useful and economical. The special large housing slot is easily able to hold the bulk created by two wires.