




1 electromechanical relay 230Vac SPDT 6A  
screw, pluggable

<b>Series</b>	CWR
<b>Code</b>	X766847
<b>Type</b>	CWRE7-0847
<b>HS code</b>	85366990
<b>INPUT TECHNICAL DATA</b>	
<b>Input rated voltage</b>	230 Vac $\pm 10\%$
<b>Current consumption</b>	4 mA $\pm 10\%$
<b>Turn ON / OFF time</b>	8 ms / 5 ms
<b>Protection circuit</b>	Free-wheel diode, Reverse polarity
<b>Connection terminal</b>	2.5 mm <sup>2</sup> screw
<b>Input channels</b>	1 pluggable
<b>OUTPUT TECHNICAL DATA</b>	
<b>Contact type</b>	SPDT, 1 form C, AgSnO <sub>2</sub>
<b>Output voltage</b>	400 Vac max., 30 Vdc max.
<b>Nominal current</b>	6 A (250 Vac), 6 A (30 Vdc)
<b>GENERAL TECHNICAL DATA</b>	
<b>Operating temperature range</b>	-20...+70°C
<b>Input / output isolation</b>	4 kVac / 60 s
<b>Protection degree</b>	IP 20
<b>Overvoltage category / pollution degree</b>	II / 2
<b>Status indication</b>	LED "Input"
<b>Housing material</b>	UL94V-0 plastic material
<b>Dimensions (LxHxD)</b>	6.2x89x77 mm
<b>Approximate weight</b>	35 g
<b>Mounting information</b>	on a rail, side by side
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
<b>Marking tag</b>	NUPUTUK50
<b>Plugin jumper</b>	CWBK7-0813 (20 poles)
<b>APPROVALS AND MARKINGS</b>	CE, 



\* Pluggable relay\* AC/DC input voltage\* SPDT contact\* Compact dimensions\* Available plug-in jumper for potential distribution  
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

## DESCRIZIONE DEL PRODOTTO

Electromechanical relay modules single channel, input rated: 230 Vac, input channels: 1 pluggable, contact type: SPDT