




**DC/DC**  
 converter 110Vdc/ 24Vdc 10A


<b>Code</b>	XCSA240FC
<b>Type</b>	CSA240FC
<b>HS code</b>	85044083
<b>INPUT TECHNICAL DATA</b>	
<b>Input rated voltage</b>	110 Vdc
<b>Input voltage DC</b>	100...130 Vdc
<b>Current consumption</b>	2.4 A (110 Vdc) ±10%
<b>Inrush peak current</b>	150 A
<b>Internal protection fuse</b>	T 5 A
<b>External protection on AC line</b>	MT: C-6 A / Fuse: T-6 A
<b>OUTPUT TECHNICAL DATA</b>	
<b>Output voltage range</b>	24 Vdc
<b>Output adjustable range</b>	23...27 Vdc
<b>Continuous current</b>	10 A at 50°C
<b>Overload limiting</b>	15 A
<b>Short circuit peak current</b>	21 A for 300 ms
<b>Ripple @ nominal ratings</b>	100 mVpp
<b>Hold up time</b>	4 ms
<b>Status indication</b>	LED "DC OK"
<b>Alarm contact</b>	dry contact, max. 1A
<b>Parallel connection</b>	possible
<b>Redundant parallel connection</b>	already fitted with internal ORing diode
<b>GENERAL TECHNICAL DATA</b>	
<b>Efficiency</b>	89% (110 Vdc)
<b>Dissipated power</b>	28W (110 Vdc)
<b>Operating temperature range</b>	-20...+60°C (derating -6 W >50°C)
<b>Input / output isolation</b>	2.1 kVdc / 60s
<b>Input / ground isolation</b>	1.41 kVdc / 60s
<b>Output / ground isolation</b>	0.75 kVdc / 60s
<b>Standard / approvals</b>	EN 60950-1
<b>EMC Standard</b>	EN 61000-6-2, EN 61000-6-4
<b>Overvoltage category / pollution degree</b>	II / 2
<b>Protection degree</b>	IP 20
<b>Connection terminal</b>	2.5 mm² / 2.5 mm²
<b>Housing material</b>	aluminium
<b>Dimensions (LxHxD)</b>	40x130x115 mm
<b>Approximate weight</b>	800 g
<b>Mounting information</b>	vertical on a rail, 10 mm from adjacent components
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
<b>Mounting rail (IEC60715/TH35-15)</b>	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
<b>APPROVALS AND MARKINGS</b>	
CE,	



\* DC wide range input\* Short circuit, overload, input and output overvoltage protections\* Over temperature protection\* Compact dimension\* Internal diode for the redundant parallel connection

1 Please refer to the datasheet for more details2 Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance3 Inrush current measured at Un with battery power supply; peak current varies according to the internal impedance of the current source and the resistance of the connections.4 The capacitors between phase and neutral, requires that the isolation tests are carried out in DC

**DESCRIZIONE DEL PRODOTTO**

CSA240FC DC/DC converter 110Vdc/ 24Vdc 10A