


1-2 phase power supply IN: 1-2x 230-400-500Vac / OUT: 12Vdc 8A



<b>Series</b>	Universal Power
<b>Code</b>	XCSW121B
<b>Type</b>	CSW121B
<b>HS code</b>	85044083
<b>INPUT TECHNICAL DATA</b>	
Input rated voltage	1-2x 230-400-500 Vac
Input voltage AC	187...550 Vac
Input voltage DC	270...725 Vdc
Frequency	47...63 Hz
Current consumption	1.1 A (230 Vac) / 0.55 A (400 Vac)
Inrush peak current	20 A
Power factor	> 0.65
External protection on AC line	MT: C-6 A / Fuse: T-4 A
<b>OUTPUT TECHNICAL DATA</b>	
Output voltage range	12 Vdc ±1%
Output adjustable range	12...15 Vdc
Continuous current	8 A (12 Vdc) - 7 A (15 Vdc)
Overload limiting	10 A for >30 s
Short circuit peak current	20 A for 0.4 s
Ripple @ nominal ratings	100 mVpp
Hold up time	20 ms (230 Vac) / 80 ms (400 Vac)
Status indication	LED "DC OK" / LED "Alarm"
Alarm contact	dry contact, max. 1A
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode
<b>GENERAL TECHNICAL DATA</b>	
Efficiency	84% (230 Vac) / 86% (400 Vac)
Dissipated power	20 W (230 Vac) / 17 W (400 Vac)
Operating temperature range	-20...+60°C (derating -3 W >45°C)
Input / output isolation	3 KVac / 60 s (SELV output)
Input / ground isolation	1.5 KVac / 60 s
Output / ground isolation	0.5 KVac / 60 s
Standard / approvals	EN 60950-1
EMC Standard	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4
Overshoot category / pollution degree	II / 2
Protection degree	IP 20
Connection terminal	2.5 mm² / 2.5 mm²
Housing material	aluminium
Dimensions (LxHxD)	40x130x115 mm
Approximate weight	600 g
Mounting information	vertical on a rail, 10 mm from adjacent components
<b>ACCESSORIES</b>	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
<b>APPROVALS AND MARKINGS</b>	
CE, ROHS	



\* Single phase and 2-phase input\* Short circuit, overload, input and output overvoltage protections\* Over temperature protection\* Suitable for applications that require high reliability and performance\* Smart alarm contact, signals when output voltage drops more than 10%\* High overload capability to ensure the protections selectivity and start-up of heavy loads  
1 Please refer to the datasheet for more details2 Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance

## DESCRIZIONE DEL PRODOTTO

1-2 phase power supply IN: 1-2x 230-400-500 Vac / OUT: 12 Vdc 8A