





3-phase filter with neutral 440VAC 50A

Series	TYT
Code	XF50TYT8
Туре	F50TYT8 (1)
HS code	85363030
GENERAL TECHNICAL DATA	
Rated voltage	440 Vac ± 10%
Continuous current	50 A
Leakage current	3 mA
Frequency	5060 Hz
Operating temperature range	-25+85°C
Isolation L / L	1.45 kVdc / 60 s (2)
Isolation L / PE	2.25 kVdc / 60 s (2)
Protection degree	IP 20
Connection terminal	fixed screw terminal blocks
Housing material	metallic
Dimensions (LxHxD)	124x194x104 mm
Approximate weight	
Mounting information	screw fixing, on metal panel
Common mode (L/PE) attenuation (dB)	
0.15 MHz	25
0.5 MHz	45
1 MHz	45
5 MHz	40
10 MHz	40
30 MHz	25
Differential mode (L/PE) attenuation (dB)	
0.15 MHz	30
0.5 MHz	50
1 MHz	50
5 MHz	40
10 MHz	40
30 MHz	30
ACCESSORIES	
APPROVALS AND MARKINGS	
	-



* Models from 36 to 100 A* Elevated attenuation from 150 kHz to 30 MHz* Elevated attenuation even on long cables 1 (1) Produced on demand, contact our sales office for availability2 (2) Isolation test need to be made in DC voltage, according to EN 60950, cause by the internal filter capacitors.

DESCRIZIONE DEL PRODOTTO

3-phase filter with neutral IN: 440 Vac 50 A