


1 solid state relay 5-24Vdc transistor 3A  
screw, fixed

<b>Series</b>	
Code	X0332060
Type	O332060
HS code	85364190
<b>INPUT TECHNICAL DATA</b>	
Input rated voltage	5-12-24 Vdc (range 4...30 Vdc)
Pull in / drop out voltage type	3 V / 1 V
Current consumption	35 mA $\pm$ 10%
Turn ON / OFF time	200 $\mu$ s / 800 $\mu$ s
Frequency	0...500 Hz
Protection circuit	Free-wheel diode
Connection terminal	2.5 mm <sup>2</sup> screw
Input channels	1 not pluggable
<b>OUTPUT TECHNICAL DATA</b>	
Contact type	transistor
Output voltage	5...60 Vdc
Nominal current	3 A (24 Vdc) at 20°C
Continuous current	10 A for 10 ms
Leakage current with signal 0	1 mA
Connection type	
Protection circuit device	free-wheel diode
<b>GENERAL TECHNICAL DATA</b>	
Operating temperature range	-20...+70°C (derating -0.5 W/°C over 20°C)
Input / output isolation	2.5 kVac / 60 s
Protection degree	IP 00
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	12x77x54 mm
Approximate weight	36 g
Mounting information	vertical on a rail, distance 5 mm from adjacent components
<b>ACCESSORIES</b>	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
Spare part relay	8904407
APPROVALS AND MARKINGS	CE



\* Not-pluggable relay\* Compact dimension  
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

## DESCRIZIONE DEL PRODOTTO

Solid state relay modules single channel, input rated: 5-12-24 Vdc (range 4...30 Vdc), input channels: 1 not pluggable, contact type: transistor