



5 port Unmanaged Ethernet Switches, transmission speed 10/100 Mbps

Series	SWE-F
Code	XSWEF05PU
Type	SWE-F-05PU
HS code	-
Version	5 – RJ45 unmanaged
Interface	
Number and type of interface	5 RJ45 ports
Connection method	Auto negotiation and auto crossing
Transmission speed	10/100 Mbps
MAC table size	1 K
Status indication	Power, Link/Speed, Link /Activity
GENERAL TECHNICAL DATA	
Power supply voltage	5...58 Vdc
Current consumption	< 300 mA
Operating temperature range	-40...+60°C
Ambient temperature range	-40...+85°C
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
Safety Standard	EN 62368-1
EMC Standard	EN/IEC 61000-3-2; EN61000-3-3
Overvoltage category /pollution degree	I / 2
Protection degree	IP20
Connection type	1.5 mm ² (screw)
Housing material	metallic
Dimensions (LxHxD)	30x118x80 mm
Approximate weight	406 g
Mounting information	on a rail, side by side
APPROVALS AND MARKINGS	
CE	
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB



DESCRIZIONE DEL PRODOTTO

5 port Unmanaged Ethernet Switches, transmission speed 10/100 Mbps