




10/100Mbps fast ethernet switch
16-RJ45, unmanaged

Series	SWE-F
Code	XSWEF16PU
Type	SWE-F-16PU
HS code	-
Version	16- RJ45 unmanaged
Interface	
Number and type of interface	16 RJ45 ports
Connection method	Auto negotiation and auto crossing
Transmission speed	10/100 Mbps
MAC table size	4 K
Status indication	Power, Link/Speed, Link /Activity
GENERAL TECHNICAL DATA	
Power supply voltage	12...58 Vdc
Current consumption	< 500 mA
Operating temperature range	-40...+60°C
Ambient temperature range	-40...+85°C
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
Safety Standard	EN 62368-1
EMC Standard	EN/IEC 61000-3-2; EN61000-3-3
Overvoltage category /pollution degree	1 / 2
Protection degree	IP20
Connection type	1.5 mm ² (screw)
Housing material	metallic
Dimensions (LxHxD)	40x170x108 mm
Approximate weight	832 g
Mounting information	on a rail, side by side
APPROVALS AND MARKINGS	CE
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB



DESCRIZIONE DEL PRODOTTO

SWE-F-16PU
10/100Mbps fast ethernet switch 16-RJ45, unmanaged