


5-port unmanaged ethernet switch 10/100 Mbps

| | |
|-----------------------------------------------|------------------------------------------------------------------------------|
| Series | SWE-T |
| Code | XSWET5PU |
| Type | SWE-T-5PU |
| HS code | 85176200 |
| Version | 5 – RJ45 unmanaged |
| Interface | |
| Number and type of interface | 5 RJ45 ports |
| Connection method | Auto negotiation, Full/Half duplex mode, auto MDI/MDI-X connection |
| Transmission speed | 10/100 Mbps |
| MAC table size | 2K |
| Status indication | Power, Link/Speed, Link /Activity |
| GENERAL TECHNICAL DATA | |
| Power supply voltage | 12...36 Vdc / 10...24 Vac |
| Current consumption | 170 mA |
| Operating temperature range | -10...+60°C |
| Ambient temperature range | -10...+60°C |
| Standards | IEEE802.3, 802.3u, 802.3x |
| Safety Standard | EN 62368-1 |
| EMC Standard | EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-6-2 |
| Overvoltage category /pollution degree | 1 / 2 |
| Protection degree | IP 30 |
| Connection type | 1.5 mm ² (screw) |
| Housing material | metallic |
| Dimensions (LxHxD) | 25x100x75 mm |
| Approximate weight | 365 g |
| Mounting information | on a rail, side by side |
| APPROVALS AND MARKINGS | |
| CE, C, E | |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| Mounting rail (IEC60715/TH35-15) | PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB |



* 5 and 8 port fast ethernet switch unmanaged* Designed to meet Level 3 (Heavy) industrial environments* Panel and DIN rail mountable

DESCRIZIONE DEL PRODOTTO

5-port unmanaged ethernet switch 10/100 Mbps