




10/100Mbps slim fast ethernet switch 8-RJ45, unmanaged

Series	SWE-T
Code	XSWET8PU
Type	SWE-T-8PU
HS code	85176200
Version	8 – RJ45 unmanaged
Interface	
Number and type of interface	8 RJ45 ports
Connection method	Auto negotiation, Full/Half duplex mode, auto MDI/MDI-X connection
Transmission speed	10/100 Mbps
MAC table size	2K
Status indication	Power, Link/Speed, Link /Activity
GENERAL TECHNICAL DATA	
Power supply voltage	12...36 Vdc / 10...24 Vac
Current consumption	170 mA
Operating temperature range	-10...+60°C
Ambient temperature range	-10...+60°C
Standards	IEEE802.3, 802.3u, 802.3x
Safety Standard	EN 62368-1
EMC Standard	EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-6-2
Overvoltage category /pollution degree	I / 2
Protection degree	IP 30
Connection type	1.5 mm ² (screw)
Housing material	metallic
Dimensions (LxHxD)	24x145x75 mm
Approximate weight	465 g
Mounting information	on a rail, side by side
APPROVALS AND MARKINGS	FC, CE,
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB



* 5 and 8 port fast ethernet switch unmanaged* Designed to meet Level 3 (Heavy) industrial environments* Panel and DIN rail mountable

DESCRIZIONE DEL PRODOTTO

SWET-8PU
10/100Mbps slim fast ethernet switch 8-RJ45, unmanaged